

Stud Fittings

3809/3909

Stud Elbow, Male BSPT Thread

ØD	C			F	G	H	L	kg
4	R1/8	3809 04 10	3909 04 10	10	10	23.5	16.5	0.020
6	R1/8	3809 06 10	3909 06 10	13	12	27.5	20	0.031
	R1/4	3809 06 13	3909 06 13	14	12	27.5	25	0.036
8	R1/8	3809 08 10	3909 08 10	14	15	32	25	0.041
	R1/4	3809 08 13	3909 08 13	14	14.5	34	25	0.046
10	R1/4	3809 10 13	3909 10 13	19	17.5	37.5	27.5	0.068
	R3/8	3809 10 17	3909 10 17	19	17.5	37.5	27.5	0.069

The body swivels for positioning purposes.

3809

Stud Elbow, Male NPT Thread

ØD	C		F	G	H	L	kg
4	NPT1/8	3809 04 11	11	10	25.5	18.5	0.021
6	NPT1/8	3809 06 11	13	12.5	29	22.5	0.025
	NPT1/4	3809 06 14	14	12.5	29	22.5	0.030
8	NPT1/8	3809 08 11	14	15	34	24	0.041
	NPT1/4	3809 08 14	14	15	34	24	0.046
10	NPT1/4	3809 10 14	19	17.5	39.5	30	0.057
	NPT3/8	3809 10 18	19	17.5	39.5	30	0.071

The body swivels for positioning purposes.

LF 3800/LF 3900

Stud standpipe 3821, 3921, 3831, 3931 can be used as illustrated, allowing:

- stock optimisation
- installation of tees and elbows where required

