

Stud Fittings

3879/3979

Compact Stud Elbow, Male BSPP Thread

ØD	C	3879		3979		F	G	H	L	kg
		3879 04 10	3879 04 13	3979 04 10	3979 04 13					
4	G1/8	3879 04 10	3879 04 13	3979 04 10	3979 04 13	10	11	22	19	0.021
	G1/4	3879 04 13	3879 04 13	3979 04 13	3979 04 13	17	11	20	19	0.026
6	G1/8	3879 06 10	3879 06 13	3979 06 10	3979 06 13	13	12	24	24	0.029
	G1/4	3879 06 13	3879 06 13	3979 06 13	3979 06 13	17	12	22	24	0.034
8	G1/8	3879 08 10	3879 08 13	3979 08 10	3979 08 13	13	15	25	25	0.035
	G1/4	3879 08 13	3879 08 13	3979 08 13	3979 08 13	17	15	25	25	0.040
10	G3/8	3879 08 17	3879 08 17	3979 08 17	3979 08 17	21	15	23	25	0.048
	G1/4	3879 10 13	3879 10 13	3979 10 13	3979 10 13	18	17	43	31	0.056
12	G3/8	3879 10 17	3879 10 17	3979 10 17	3979 10 17	21	17	40	31	0.067
	G1/4	3879 12 13	3879 12 13	3979 12 13	3979 12 13	17	20	33	33	0.075
12	G3/8	3879 12 17	3879 12 17	3979 12 17	3979 12 17	21	20	33	33	0.082
	G1/2	3879 12 21	3879 12 21	3979 12 21	3979 12 21	24	20	30	33	0.094

The body swivels for positioning purposes.
Max. 20 bar

