


Stud Fittings

3889/3989


Compact Stud Elbow, Male BSPT Thread

 	Stainless steel 316L, FKM		ØD	C			F	G	H	L	kg
	4	R1/8	3889 04 10	3989 04 10			13	10	18	17	0.018
		R1/4	3889 04 13	3989 04 13			17	10	19.5	16.5	0.025
	6	R1/8	3889 06 10	3989 06 10			13	12	21.5	20.5	0.026
		R1/4	3889 06 13	3989 06 13			14	12	21.5	20.5	0.032
	8	R1/8	3889 08 10	3989 08 10			14	15	24	22	0.036
		R1/4	3889 08 13	3989 08 13			14	15	24	22	0.041
	10	R1/4	3889 10 13	3989 10 13			17	17.5	28.5	27.5	0.057
		R3/8	3889 10 17	3989 10 17			19	17.5	28.5	27.5	0.062
	12	R1/4	3889 12 13	3989 12 13			22	20	33.5	30	0.086
		R3/8	3889 12 17	3989 12 17			22	20	33.5	30	0.088
		R1/2	3889 12 21	3989 12 21			22	20	33.5	33	0.095

The body swivels for positioning purposes.
Max. 20 bar

3889

Compact Stud Elbow, Male NPT Thread


 	Stainless steel 316L, FKM		ØD	C			F	G	H	L	kg
	4	NPT1/8	3889 04 11				13	10	17.5	19	0.019
		NPT1/8	3889 06 11				13	12.5	20	22.5	0.020
	6	NPT1/4	3889 06 14				14	12.5	20	22.5	0.033
		NPT1/8	3889 08 11				13	15	25	24	0.037
	8	NPT1/4	3889 08 14				14	15	24	24	0.037
		NPT1/4	3889 10 14				17	17.5	27.5	27.5	0.058
	10	NPT3/8	3889 10 18				19	17.5	28.5	26.5	0.067
		NPT1/4	3889 12 14				22	20	31.5	32.5	0.070
	12	NPT3/8	3889 12 18				22	20	32.5	32.5	0.087
		NPT1/2	3889 12 22				22	20	27.5	32.5	0.072

The body swivels for positioning purposes.
Max. 20 bar

3889

Compact Stud Elbow, Male NPT Thread

Inch

 	Stainless steel 316L, FKM		ØD	C			F	G	H	L	kg
	3/16	NPT1/8	3889 55 11				10	9.9	20.6	19.6	0.019
		NPT1/4	3889 55 14				14	9.9	20.6	19.6	0.022
	1/4	NPT1/8	3889 56 11				13	11.9	21.6	23.1	0.026
		NPT1/4	3889 56 14				14	11.9	21.6	23.1	0.031
	3/8	NPT1/4	3889 60 14				17	17.5	28.4	30.5	0.059
		NPT3/8	3889 60 18				19	17.5	28.4	30.5	0.062
	1/2	NPT1/4	3889 62 14				22	20.1	34	33	0.086
		NPT3/8	3889 62 18				22	20.1	34	33	0.088
	1/2	NPT1/2	3889 62 22				22	20.1	27.2	33	0.091

The body swivels for positioning purposes; 5/32" (4 mm) and 5/16" (8 mm) also available.
Max. 20 bar