


Stud Fittings

3889/3989

Compact Stud Elbow, Male BSPT Thread




ØD	C			F	G	H	L	kg
4	R1/8	3889 04 10	3989 04 10	13	10	18	17	0.018
	R1/4	3889 04 13	3989 04 13	17	10	19.5	16.5	0.025
6	R1/8	3889 06 10	3989 06 10	13	12	21.5	20.5	0.026
	R1/4	3889 06 13	3989 06 13	14	12	21.5	20.5	0.032
8	R1/8	3889 08 10	3989 08 10	14	15	24	22	0.036
	R1/4	3889 08 13	3989 08 13	14	15	24	22	0.041
10	R1/4	3889 10 13	3989 10 13	17	17.5	28.5	27.5	0.057
	R3/8	3889 10 17	3989 10 17	19	17.5	28.5	27.5	0.062
12	R1/4	3889 12 13	3989 12 13	22	20	33.5	30	0.086
	R3/8	3889 12 17	3989 12 17	22	20	33.5	30	0.088
	R1/2	3889 12 21	3989 12 21	22	20	33.5	33	0.095

The body swivels for positioning purposes.
Max. 20 bar

3889

Compact Stud Elbow, Male NPT Thread




ØD	C		F	G	H	L	kg
4	NPT1/8	3889 04 11	13	10	17.5	19	0.019
6	NPT1/8	3889 06 11	13	12.5	20	22.5	0.020
	NPT1/4	3889 06 14	14	12.5	20	22.5	0.033
8	NPT1/8	3889 08 11	13	15	25	24	0.037
	NPT1/4	3889 08 14	14	15	24	24	0.037
10	NPT1/4	3889 10 14	17	17.5	27.5	27.5	0.058
	NPT3/8	3889 10 18	19	17.5	28.5	26.5	0.067
12	NPT1/4	3889 12 14	22	20	31.5	32.5	0.070
	NPT3/8	3889 12 18	22	20	32.5	32.5	0.087
	NPT1/2	3889 12 22	22	20	27.5	32.5	0.072

The body swivels for positioning purposes.
Max. 20 bar

3889

Compact Stud Elbow, Male NPT Thread

Inch



ØD	C		F	G	H	L	kg
3/16	NPT1/8	3889 55 11	10	9.9	20.6	19.6	0.019
	NPT1/4	3889 55 14	14	9.9	20.6	19.6	0.022
1/4	NPT1/8	3889 56 11	13	11.9	21.6	23.1	0.026
	NPT1/4	3889 56 14	14	11.9	21.6	23.1	0.031
3/8	NPT1/4	3889 60 14	17	17.5	28.4	30.5	0.059
	NPT3/8	3889 60 18	19	17.5	28.4	30.5	0.062
1/2	NPT1/4	3889 62 14	22	20.1	34	33	0.086
	NPT3/8	3889 62 18	22	20.1	34	33	0.088
	NPT1/2	3889 62 22	22	20.1	27.2	33	0.091

The body swivels for positioning purposes; 5/32" (4 mm) and 5/16" (8 mm) also available.
Max. 20 bar