


Stud Fittings

3899/3999
Stud Elbow, Male BSPP and Metric Thread

		Stainless steel 316L, FKM				F	G	H	L	kg
ØD	C			F	G	H	L	L	L	kg
4	M5x0.8	3899 04 19	3999 04 19	10	10	26	18	0.019		
	G1/8	3899 04 10	3999 04 10	13	10	27	19	0.021		
	G1/4	3899 04 13	3999 04 13	17	10	27	19	0.018		
6	M5x0.8	3899 06 19	3999 06 19	13	12	33	24	0.031		
	G1/8	3899 06 10	3999 06 10	6	12	33	24	0.031		
	G1/4	3899 06 13	3999 06 13	17	12	32	24	0.035		
8	G1/8	3899 08 10	3999 08 10	14	15	35	25	0.039		
	G1/4	3899 08 13	3999 08 13	17	15	35	25	0.044		
	G3/8	3899 08 17	3999 08 17	21	15	34.5	25	0.048		
10	G1/4	3899 10 13	3999 10 13	19	17	43	31	0.068		
	G3/8	3899 10 17	3999 10 17	21	17	42	31	0.072		

The body swivels for positioning purposes.



LF 3800/LF 3900

Stud standpipe 3821, 3921, 3831, 3931 can be used as illustrated, allowing:

- stock optimisation
- installation of tees and elbows where required

