


Triple-Lok®

C6MX Swivel nut elbow

Triple-Lok® 37° Flare end / Triple-Lok® 37° Flare female swivel end
SAE 070221 MS51521



Tube O.D.		Thread UN/UNF-2A T	Thread UN/UNF-2B T6	C3 mm	D mm	M mm	M5 mm	M10 mm	Y mm	Weight (steel) g/1 piece	Triple-Lok® Steel	Triple-Lok® Stainless Steel	PN (bar)	
mm	in.												S	SS
6	3/16	3/8-24	3/8-24	14	3	21	25	18	11	27	3 C6X-S		500	—
8	1/4	7/16-20	7/16-20	17	4.4	23	25	17	13	37	4C6MXS	4C6MXSS	500	350
10	5/16	1/2-20	1/2-20	19	6	24	25	17	14	43	5C6MXS	5C6MXSS	420	350
12	3/8	9/16-18	9/16-18	22	7.5	27	27	22	19	54	6C6MXS	6C6MXSS	350	350
	1/2	3/4-16	3/4-16	27	9.9	32	34	24	22	105	8C6MXS	8C6MXSS	350	350
14, 15, 16	5/8	7/8-14	7/8-14	32	12	37	40	28	27	162	10C6MXS	10C6MXSS	350	350
18, 20	3/4	1 1/16-12	1 1/16-12	35	15.5	42	42	30	33	260	12C6MXS	12C6MXSS	350	350
22	7/8	1 3/16-12	1 3/16-12	38	18.3	46	45	34	33	293	14 C6X-S		250	—
25	1	1 5/16-12	1 5/16-12	40	21.5	46	52	37	33	420	16C6MXS	16C6MXSS	250	250
28, 30, 32	1 1/4	1 5/8-12	1 5/8-12	47	27.5	52	59	43	41	679	20C6MXS	20C6MXSS	250	210
35, 38	1 1/2	1 7/8-12	1 7/8-12	57	33	59	67	47	48	747	24 C6X-S	24C6MXSS	170	140
	2	2 1/2-12	2 1/2-12	73	45	78	87	62	64	920	32 C6X-S		110	—

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.