


CC87OMLO Extended male stud elbow

O-Lok® ORFS tube end / Male metric thread – O-ring (ISO 6149-2)

SAE 52M1587 ISO 8434-3 SDEL



| Tube O.D. | | Thread metric T87 | Thread UN/UNF-2A T | D mm | D2 mm | M mm | N mm | XX mm | JJ mm | B1 mm | Weight (steel) g/1 piece | O-Lok® Steel | PN (bar) |
|------------|-----------|-------------------|--------------------|------|-------|------|------|-------|-------|-------|--------------------------|-----------------------|----------|
| mm | in. | | | | | | | | | | | | |
| 6 | 1/4 | M 12×1.5 | 9/16-18 | 4.5 | 4 | 23 | 56 | 45 | 19 | 17 | 44 | 4M12CC87OMLOS | 420 |
| 8, 10 | 5/16, 3/8 | M 14×1.5 | 11/16-16 | 6.5 | 6 | 25 | 56 | 45 | 19 | 19 | 51 | 6M14CC87OMLOS | 420 |
| 8, 10 | 5/16, 3/8 | M 16×1.5 | 11/16-16 | 6.5 | 7 | 25 | 67 | 54 | 22 | 22 | 51 | 6M16CC87OMLOS | 420 |
| 12 | 1/2 | M 18×1.5 | 13/16-16 | 9.5 | 9 | 28 | 75 | 61 | 22 | 24 | 150 | 8M18CC87OMLOS | 420 |
| 12 | 1/2 | M 22×1.5 | 13/16-16 | 9.5 | 12 | 32 | 88 | 74 | 27 | 27 | 150 | 8M22CC87OMLOS | 420 |
| 14, 15, 16 | 5/8 | M 22×1.5 | 1-14 | 12.5 | 12 | 34 | 88 | 74 | 27 | 27 | 160 | 10M22CC87OMLOS | 420 |
| 18, 20 | 3/4 | M 27×2.0 | 1 3/16-12 | 15.5 | 15 | 38 | 101 | 83 | 33 | 32 | 290 | 12M27CC87OMLOS | 420 |
| 22, 25 | 1 | M 33×2.0 | 1 7/16-12 | 20.5 | 20 | 41 | 115 | 96 | 41 | 41 | 480 | 16M33CC87OMLOS | 420 |
| 28, 30, 32 | 1 1/4 | M 42×2.0 | 1 11/16-12 | 26 | 26 | 45 | 127 | 107 | 41 | 50 | 630 | 20M42CC87OMLOS | 280 |



Product delivered with NBR TRAP seal. Replacement of TRAP seal is with a standard NBR O-ring – see page J74–J75.

Part numbers shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.