
CC87OMLO Extended male stud elbow

O-Lok® ORFS tube end / Male metric thread – O-ring (ISO 6149-2)
SAE 52M1587 ISO 8434-3 SDEL



Tube O.D. mm	Tube O.D. in.	Thread metric T87	Thread UN/UNF-2A T	D mm	D2 mm	M mm	N mm	XX mm	JJ mm	B1 mm	Weight (steel) g/1 piece	O-Lok® Steel	PN (bar)
6	1/4	M 12×1.5	9/16-18	4.5	4	23	56	45	19	17	44	**4M12CC87OMLOS**	420
8, 10	5/16, 3/8	M 14×1.5	11/16-16	6.5	6	25	56	45	19	19	51	**6M14CC87OMLOS**	420
8, 10	5/16, 3/8	M 16×1.5	11/16-16	6.5	7	25	67	54	22	22	51	**6M16CC87OMLOS**	420
12	1/2	M 18×1.5	13/16-16	9.5	9	28	75	61	22	24	150	**8M18CC87OMLOS**	420
12	1/2	M 22×1.5	13/16-16	9.5	12	32	88	74	27	27	150	**8M22CC87OMLOS**	420
14, 15, 16	5/8	M 22×1.5	1-14	12.5	12	34	88	74	27	27	160	**10M22CC87OMLOS**	420
18, 20	3/4	M 27×2.0	1 3/16-12	15.5	15	38	101	83	33	32	290	**12M27CC87OMLOS**	420
22, 25	1	M 33×2.0	1 7/16-12	20.5	20	41	115	96	41	41	480	**16M33CC87OMLOS**	420
28, 30, 32	1 1/4	M 42×2.0	1 11/16-12	26	26	45	127	107	41	50	630	**20M42CC87OMLOS**	280

Product delivered with NBR TRAP seal. Replacement of TRAP seal is with a standard NBR O-ring – see page J74–J75.

Part numbers shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10}$ = PN (MPa)

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.

J

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark