


Adapters

CDM Male female thread elbow

Male NPTF* thread (SAE J476) / Female NPTF* thread (SAE J476)

SAE 140239

*Stainless Steel = NPT to prevent galling



| Thread NPT/NPTF PTM | Thread NPT/NPTF PTF | D mm | N mm | N1 mm | Y mm | Weight (steel) g/1 piece | Adapter Steel | Adapter Stainless Steel | PN (bar) | |
|---------------------------|---------------------------|---------|---------|----------|---------|--------------------------------|-----------------------|----------------------------|----------|-----|
| | | | | | | | | | S | SS |
| 1/8-27 | 1/8-27 | 4.8 | 20 | 17 | 14 | 30 | 1/8 CD-S | 1/8 CD-SS | 350 | 350 |
| 1/4-18 | 1/4-18 | 7 | 28 | 22 | 19 | 77 | 1/4 CDMS | 1/4 CD-SS | 350 | 350 |
| 1/4-18 | 1/8-27 | 7.1 | 28 | 17 | 14 | 33 | 1/4 X 1/8 CD-S | 1/4 X 1/8 CD-SS | 350 | 350 |
| 3/8-18 | 3/8-18 | 10 | 31 | 26 | 22 | 96 | 3/8 CDMS | 3/8 CD-SS | 310 | 310 |
| 3/8-18 | 1/4-18 | 10.3 | 31 | 22 | 19 | 79 | 3/8 X 1/4 CD-S | 3/8 X 1/4 CD-SS | 350 | 350 |
| 3/8-18 | 1/2-14 | 10.3 | 33 | 31 | 27 | 260 | 3/8 X 1/2 CD-S | 3/8 X 1/2 CD-SS | 210 | 210 |
| 1/2-14 | 1/2-14 | 13.5 | 37 | 31 | 27 | 174 | 1/2 CD-S | 1/2 CD-SS | 210 | 210 |
| 1/2-14 | 3/8-18 | 13.5 | 38 | 32 | 22 | 96 | 1/2 X 3/8 CD-S | 1/2 X 3/8 CD-SS | 310 | 310 |
| 1/2-14 | 3/4-14 | 13.5 | 40 | 35 | 33.3 | 319 | 1/2 X 3/4 CD-S | 1/2 X 3/4 CD-SS | 210 | 210 |
| 3/4-14 | 3/4-14 | 18.3 | 40 | 35 | 33.3 | 285 | 3/4 CD-S | 3/4 CD-SS | 210 | 210 |
| 3/4-14 | 1/2-14 | 18.3 | 40 | 31 | 27 | 164 | 3/4 X 1/2 CD-S | 3/4 X 1/2 CD-SS | 210 | 210 |
| 1-11.5 | 1-11.5 | 23.8 | 50 | 41 | 47.6 | 515 | 1 CD-S | 1 CD-SS | 125 | 120 |
| 1 1/4-11.5 | 1 1/4-11.5 | 31.8 | 61 | 43 | 47.6 | 978 | 1 1/4 CD-S | 1 1/4 CD-SS | 100 | 100 |
| 1 1/2-11.5 | 1 1/2-11.5 | 38.1 | 67 | 53 | 63.5 | 1679 | 1 1/2 CD-S | 1 1/2 CD-SS | 100 | 100 |

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{PN \text{ (bar)}}{10} = PN \text{ (MPa)}$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.

