


## Triple-Lok®

### F65OMX Swivel male stud

Triple-Lok® 37° Flare female swivel end / Male UN/UNF thread – O-ring (ISO 11926)



Tube O.D.		Thread UNF T5	Thread UN/UNF-2B T6	C4 mm	C3 mm	D mm	D2 mm	L5 mm	LL mm	Weight (steel) g/1 piece	Triple-Lok® Steel	PN (bar)
mm	in.											
6	1/4	7/16-20	7/16-20	14	14	4.4	4.4	33	15	27	<b>4F65OMXS</b>	500
8	5/16	1/2-20	1/2-20	17	17	6	6	35	17	30	<b>5F65OMXS</b>	420
10	3/8	9/16-18	9/16-18	17	19	7.5	7.5	38	18	35	<b>6F65OMXS</b>	350
12	1/2	3/4-16	3/4-16	22.2	22	9.9	9.9	41.5	19	64	<b>8 F65OX-S</b>	350
14, 15, 16	5/8	7/8-14	7/8-14	25.4	25.4	12.3	12.3	46	20.5	112	<b>10 F65OX-S</b>	350
18, 20	3/4	1 1/16-12	1 1/16-12	28.6	28.6	15.5	15.5	54	25	183	<b>12 F65OX-S</b>	350
25	1	1 5/16-12	1 5/16-12	38	38	21.4	21.4	58	27	234	<b>16 F65OX-S</b>	250
28, 30, 32	1 1/4	1 5/8-12	1 5/8-12	51	51	27.5	27.5	63	32	500	<b>20 F65OX-S</b>	250

Steel, stainless steel and brass Triple-Lok® parts are delivered with NBR elastomeric seals as standard. For more details on other seal materials see page K92.

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.