
## G4MLOSMO Pressure gauge connector

O-Lok® ORFS tube end / Female BSPP gauge thread (ISO 1179-1)




| Tube O.D. mm | Tube O.D. in. | Thread BSPP T4 | Thread UN/UNF-2A T | E mm | H mm | HH mm | Weight (steel) g/1 piece | O-Lok® Steel | O-Lok® Stainless Steel | PN (bar) S | PN (bar) SS |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 6 | 1/4 | 1/4-19 | 9/16-18 | 18 | 17 | 27 | 32 | **4-4G4MLOSMO** | **4-4G4MLOSSMO** | 400 | 400 |
| 6 | 1/4 | 1/2-14 | 9/16-18 | 27 | 30 | 37 | 80 | **4-8G4MLOSMO** | **4-8G4MLOSSMO** | 400 | 400 |
| 8, 10 | 3/8 | 1/4-19 | 11/16-16 | 17 | 19 | 28 | 49 | **6G4MLOSMO** | **6G4MLOSSMO** | 400 | 400 |
| 8, 10 | 3/8 | 1/2-14 | 11/16-16 | 27 | 30 | 38 | 107 | **6-8G4MLOSMO** | **6-8G4MLOSSMO** | 400 | 400 |
| 12 | 1/2 | 1/4-19 | 13/16-16 | 17 | 22 | 30 | 60 | **8-4G4MLOSMO** | **8-4G4MLOSSMO** | 280 | 280 |
| 12 | 1/2 | 1/2-14 | 13/16-16 | 27 | 30 | 40 | 80 | **8-8G4MLOSMO** | **8-8G4MLOSSMO** | 280 | 280 |

Product delivered with NBR TRAP seal. Replacement of TRAP seal is with a standard NBR O-ring – see page J74–J75.

Part numbers shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10}$ = PN (MPa)

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark