


DIN fittings



GE-M Male stud connector

Male metric thread – metal sealing edge (ISO 9974) / EO 24° cone end



	D1										Weight		PN (bar) ¹⁾			
Series		T	D3	D4	L1	L2	L3	L4	S1	S2	g/1 piece	Order code*	CF	71	MS	
L ³⁾	06	M 10×1.0	4	14	23.5	8.5	8	23	14	14	13	GE06LM	315	315	200	
	08	M 12×1.5	6	17	29.0	10.0	12	25	17	17	22	GE08LM	315	315	200	
	10	M 14×1.5	7	19	30.0	11.0	12	26	19	19	31	GE10LM	315	315	200	
	10	M 10×1.0	4	14	25.5	10.5	8	25	17	19	20	GE10LM10X1	315	315		
	10	M 12×1.5	6	17	30.0	11.0	12	26	17	19	25	GE10LM12X1.5	315	315		
	10	M 16×1.5	8	21	31.5	12.0	12	27	22	19	41	GE10LM16X1.5	315	315		
	10	M 18×1.5	8	23	31.5	12.5	12	27	24	19	50	GE10LM18X1.5	315	315		
	10	M 22×1.5	8	27	35.0	14.0	14	29	27	19	72	GE10LM22X1.5	315	315		
	12	M 14×1.5	7	19	30.0	11.0	12	26	19	22	30	GE12LM14X1.5	315	315		
	12	M 16×1.5	9	21	31.5	12.5	12	27	22	22	40	GE12LM	315	315		
	12	M 18×1.5	10	23	31.5	12.5	12	27	24	22	47	GE12LM18X1.5	315	315		
	12	M 22×1.5	10	27	35.0	14.0	14	29	27	22	76	GE12LM22X1.5	315	315		
	15	M 16×1.5	9	21	32.0	13.0	12	28	24	27	50	GE15LM16X1.5	250	250		
	15	M 18×1.5	11	23	32.5	13.5	12	29	24	27	52	GE15LM	250	250	160	
	15	M 22×1.5	12	27	36.0	15.0	14	30	27	27	77	GE15LM22X1.5	250	250		
	18	M 18×1.5	11	23	33.5	14.0	12	30	27	32	68	GE18LM18X1.5	250	250		
	18	M 22×1.5	14	27	36.0	14.5	14	31	27	32	77	GE18LM	250	250	160	
	22	M 22×1.5	14	27	38.0	16.5	14	33	32	36	92	GE22LM22X1.5	160	160		
	22	M 26×1.5	18	31	40.0	16.5	16	33	32	36	102	GE22LM	160	160	100	
	28	M 33×2.0	23	39	43.0	17.5	18	34	41	41	168	GE28LM	160	160	100	
	35	M 42×2.0	30	49	48.0	17.5	20	39	50	50	280	GE35LM	160	160	100	
	42	M 48×2.0	36	55	52.0	19.0	22	42	55	60	354	GE42LM	160	160	100	
	S ⁴⁾	06	M 12×1.5	4	17	32.0	13.0	12	28	17	17	30	GE06SM	400	400	250
		06	M 14×1.5	4	19	34.0	15.0	12	30	19	17	42	GE06SM14X1.5	400	400	
08		M 14×1.5	5	19	34.0	15.0	12	30	19	19	43	GE08SM	400	400	250	
10		M 16×1.5	7	21	34.5	15.0	12	31	22	22	54	GE10SM	400	400	250	
12		M 18×1.5	8	23	36.5	17.0	12	33	24	24	72	GE12SM	400	400	250	
12		M 14×1.5	5	19	36.0	16.5	12	33	22	24	60	GE12SM14X1.5	400	400		
12		M 22×1.5	8	27	39.0	17.5	14	34	27	24	103	GE12SM22X1.5	400	400		
14		M 20×1.5	10	25	41.0	19.0	14	37	27	27	95	GE14SM	400	400	250	
16		M 18×1.5	8	23	38.5	18.0	12	36	27	30	88	GE16SM18X1.5	400	400		
16		M 22×1.5	12	27	41.0	18.5	14	37	27	30	97	GE16SM	400	400	250	
20		M 27×2.0	16	32	47.0	20.5	16	42	32	36	155	GE20SM	400	400	250	
25		M 33×2.0	20	39	53.0	23.0	18	47	41	46	268	GE25SM	250	250	160	
30		M 42×2.0	25	49	57.0	23.5	20	50	50	50	421	GE30SM	160	160	100	
38		M 48×2.0	32	55	64.0	26.0	22	57	55	60	568	GE38SM	160	160	100	

¹⁾ Pressure shown = item deliverable

³⁾ L = light series; ⁴⁾ S = heavy series

PN (bar) = PN (MPa)
10

Delivery without nut and ring. Information on ordering complete fittings see page I7.

*Please add the suffixes below according to the material/surface required.

Order code suffixes		
Material	Suffix surface and material	Example
Steel, zinc plated, Cr(VI)-free	CFX	GE16SMCFX
Stainless Steel	71X	GE16SM71X
Brass	MSX	GE16SMMSX

