


## JMTX Union tee

Triple-Lok® 37° Flare end (three ends)  
SAE 070401 MS51510



Tube O.D.		Thread UN/UNF-2A T	D mm	M mm	Y mm	Weight (steel) g/1 piece	Triple-Lok® Steel	Triple-Lok® Stainless Steel	Triple-Lok® Brass	PN (bar)	
mm	in.									S	SS
6	1/8	5/16-24	1.6	19.5	8	25	<b>2 JTX-S</b>			500	—
	3/16	3/8-24	3	21	11	30	<b>3 JTX-S</b>			500	—
	1/4	7/16-20	4.4	22.5	11	33	<b>4JMTXS</b>	<b>4JMTXSS</b>	<b>4 JTX-B</b>	500	350
	5/16	1/2-20	6	24	13	42	<b>5JMTXS</b>	<b>5JMTXSS</b>	<b>5 JTX-B</b>	420	350
8	3/8	9/16-18	7.5	27	14	53	<b>6JMTXS</b>		<b>6 JTX-B</b>	420	350
	1/2	3/4-16	9.9	32	19	118	<b>8JMTXS</b>	<b>8JMTXSS</b>	<b>8 JTX-B</b>	420	350
14, 15, 16	5/8	7/8-14	12.3	27	22	182	<b>10JMTXS</b>	<b>10JMTXSS</b>	<b>10 JTX-B</b>	350	350
	3/4	1 1/16-12	15.5	42	27	291	<b>12JMTXS</b>	<b>12JMTXSS</b>	<b>12 JTX-B</b>	350	350
18, 20	7/8	1 3/16-12	18	45.8	33	403	<b>14 JTX-S</b>		<b>14 JTX-B</b>	280	245
	1	1 5/16-12	21.5	46	33	415	<b>16JMTXS</b>	<b>16JMTXSS</b>	<b>16 JTX-B</b>	280	280
28, 30, 32	1 1/4	1 5/8-12	27.5	52	41	706	<b>20JMTXS</b>	<b>20JMTXSS</b>	<b>20 JTX-B</b>	280	210
	1 1/2	1 7/8-12	33	59	48	990	<b>24 JTX-S</b>	<b>24JMTXSS</b>	<b>24 JTX-B</b>	210	140
35, 38	1 3/4	2 1/4-12	39	74.5	63	2270	<b>28 JTX-S</b>			140	—
	2	2 1/2-12	45	78	63.5	2450	<b>32 JTX-S</b>			140	—



Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Pressure ratings – PN shown, apply to Steel and Stainless Steel versions of the product.

For Brass parts reduce pressures by 35%.

Union tee reducing up on request.

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.