


## PNMTX Plug

Triple-Lok® 37° Flare end plug  
SAE 070109 MS51518



Tube O.D.		Thread UN/UNF-2A T	C mm	L mm	Weight (steel) g/1 piece	Triple-Lok® Steel	Triple-Lok® Stainless Steel	PN (bar)	
mm	in.							S	SS
6	1/8	5/16-24	11	18	9	<b>2 PNTX-S</b>		500	—
	3/16	3/8-24	11	19	10	<b>3 PNTX-S</b>		500	—
	1/4	7/16-20	13	21	10	<b>4PNMTXS</b>	<b>4PNMTXSS</b>	500	350
	5/16	1/2-20	14	21	14	<b>5PNMTXS</b>	<b>5PNMTXSS</b>	420	350
8	3/8	9/16-18	16	21	19	<b>6 PNTX-S</b>	<b>6PNMTXSS</b>	420	350
14, 15, 16	1/2	3/4-16	19	24	39	<b>8PNMTXS</b>	<b>8PNMTXSS</b>	420	350
	5/8	7/8-14	24	28	60	<b>10PNMTXS</b>	<b>10PNMTXSS</b>	350	350
	3/4	1 1/16-12	27	33	93	<b>12PNMTXS</b>	<b>12PNMTXSS</b>	350	350
	7/8	1 3/16-12	31.75	33	95	<b>14 PNTX-S</b>	<b>14PNMTXSS</b>	280	280
	1	1 5/16-12	35	34	98	<b>16 PNTX-S</b>	<b>16PNMTXSS</b>	280	280
28, 30, 32	1 1/4	1 5/8-12	42.8	37	269	<b>20 PNTX-S</b>	<b>20PNMTXSS</b>	280	210
	1 1/2	1 7/8-12	51	42	360	<b>24 PNTX-S</b>	<b>24PNMTXSS</b>	210	140
35, 38	2	2 1/2-12	66.6	52	470	<b>32 PNTX-S</b>		140	—



Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.