
## S6MLO Swivel nut branch tee

O-Lok® ORFS female swivel end / O-Lok® ORFS tube ends
SAE 52M0433 ISO 8434-3 SWBT




| Tube O.D. mm | Tube O.D. in. | Thread UN/UNF-2A T | Thread UN/UNF-2B T6 | AAA mm | B mm | D mm | D1 mm | JJ* mm | M mm | Weight (steel) g/1 piece | O-Lok® Steel | O-Lok® Stainless Steel | PN (bar) S | PN (bar) SS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 6 | 1/4 | 9/16-18 | 9/16-18 | 26 | 17 | 4.5 | 4 | 14 | 22 | 66 | **4S6MLOS** | **4S6MLOSS** | 500 | 420 |
| 8, 10 | 5/16, 3/8 | 11/16-16 | 11/16-16 | 29 | 22 | 6.5 | 6.5 | 19 | 25 | 125 | **6S6MLOS** | **6S6MLOSS** | 630 | 420 |
| 12 | 1/2 | 13/16-16 | 13/16-16 | 38 | 24 | 9.5 | 9 | 19 | 28 | 150 | **8S6MLOS** | **8S6MLOSS** | 630 | 420 |
| 14, 15, 16 | 5/8 | 1-14 | 1-14 | 41 | 30 | 12.5 | 11.5 | 27 | 33 | 233 | **10S6MLOS** | **10S6MLOSS** | 420 | 420 |
| 18, 20 | 3/4 | 1 3/16-12 | 1 3/16-12 | 47 | 35 | 15.5 | 14 | 30 | 38 | 383 | **12 S6LO-S** | **12S6MLOSS** | 420 | 420 |
| 22, 25 | 1 | 1 7/16-12 | 1 7/16-12 | 54 | 41 | 20.5 | 20 | 36 | 42 | 518 | **16 S6LO-S** | **16S6MLOSS** | 420 | 420 |
| 28, 30, 32 | 1 1/4 | 1 11/16-12 | 1 11/16-12 | 58 | 48 | 26 | 26 | 41 | 45 | 775 | **20 S6LO-S** | **20S6MLOSS** | 350 | 280 |
| 35, 38 | 1 1/2 | 2-12 | 2-12 | 61 | 57 | 32 | 32 | 48 | 49 | 933 | **24 S6LO-S** | **24S6MLOSS** | 280 | 280 |

Product delivered with NBR TRAP seal. Replacement of TRAP seal is with a standard NBR O-ring – see page J74–J75.

Part numbers shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.
*JJ may vary in stainless steel

J



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark