


Triple-Lok®

V5OMX 45° Male stud elbow

Triple-Lok® 37° Flare end / Male UNF thread O-ring (ISO 11926)
SAE 070320 MS51528



| Tube O.D. | | Thread UN/UNF-2A T5 | Thread UN/UNF-2A T | C4 mm | D mm | D2 mm | M2 mm | M8 mm | XX mm | Y mm | Weight (steel) g/1 piece | Triple-Lok® Steel | Triple-Lok® Stainless Steel | PN (bar) | |
|------------|-------|---------------------|--------------------|-------|------|-------|-------|-------|-------|------|--------------------------|-------------------|-----------------------------|----------|-----|
| mm | in. | | | | | | | | | | | | | S | SS |
| 6 | 1/4 | 7/16-20 | 7/16-20 | 14.3 | 4.4 | 4.4 | 18 | 27 | 16 | 11 | 34 | 4 V5OX-S | 4 V5OX-SS | 420 | 350 |
| 8 | 5/16 | 1/2-20 | 1/2-20 | 16 | 6 | 6 | 20 | 27 | 16 | 14 | 42 | 5 V5OX-S | 5 V5OX-SS | 420 | 350 |
| 10 | 3/8 | 9/16-18 | 9/16-18 | 17 | 7.5 | 7.5 | 21 | 29 | 17 | 14 | 52 | 6V5OMXS | 6 V5OX-SS | 420 | 350 |
| 10 | 3/8 | 3/4-16 | 9/16-18 | 22.2 | 7.5 | 9.9 | 22 | 23 | 19 | 19 | 104 | 6-8 V5OX-S | 6-8 V5OX-SS | 420 | 350 |
| 12 | 1/2 | 3/4-16 | 3/4-16 | 22.2 | 9.9 | 9.9 | 25 | 33 | 19 | 19 | 104 | 8 V5OX-S | 8 V5OX-SS | 420 | 350 |
| 12 | 1/2 | 9/16-18 | 3/4-16 | 17.5 | 9.9 | 7.5 | 25 | 28 | 16 | 19 | 98 | 8-6 V5OX-S | 8-6 V5OX-SS | 420 | 350 |
| 12 | 1/2 | 7/8-14 | 3/4-16 | 25.4 | 9.9 | 12.3 | 25 | 39 | 23 | 22 | 148 | 8-10 V5OX-S | 8-10 V5OX-SS | 350 | 350 |
| 14, 15, 16 | 5/8 | 7/8-14 | 7/8-14 | 25.4 | 12.3 | 12.3 | 28 | 39 | 23 | 22 | 157 | 10 V5OX-S | 10 V5OX-SS | 350 | 350 |
| 14, 15, 16 | 5/8 | 3/4-16 | 7/8-14 | 22.2 | 12.3 | 9.9 | 28 | 35 | 21 | 22 | 157 | 10-8 V5OX-S | 10-8 V5OX-SS | 350 | 350 |
| 18, 20 | 3/4 | 1 1/16-12 | 1 1/16-12 | 31.8 | 15.5 | 15.5 | 33 | 44 | 26 | 27 | 258 | 12 V5OX-S | 12 V5OX-SS | 350 | 350 |
| 18, 20 | 3/4 | 7/8-14 | 1 1/16-12 | 25.4 | 15.5 | 12.5 | 33 | 40 | 25 | 27 | 227 | 12-10 V5OX-S | 12-10 V5OX-SS | 350 | 350 |
| 22 | 7/8 | 1 3/16-12 | 1 3/16-12 | 35 | 18.3 | 18.3 | 37 | 47 | 30 | 33.3 | 275 | 14 V5OX-S | | 280 | — |
| 25 | 1 | 1 5/16-12 | 1 5/16-12 | 38 | 21.4 | 21.4 | 37 | 47 | 30 | 33.3 | 375 | 16 V5OX-S | 16 V5OX-SS | 280 | 280 |
| 25 | 1 | 1 5/16-12 | 1 1/16-12 | 31.8 | 21.4 | 15.5 | 37 | 47 | 31 | 33.3 | 277 | 16-12 V5OX-S | | 280 | 280 |
| 28, 30, 32 | 1 1/4 | 1 5/8-12 | 1 5/8-12 | 47.6 | 27.4 | 27.4 | 40 | 49 | 31 | 41 | 570 | 20 V5OX-S | 20 V5OX-SS | 280 | 210 |
| 35, 38 | 1 1/2 | 1 7/8-12 | 1 7/8-12 | 54 | 33.3 | 33.3 | 45 | 49 | 31 | 47.6 | 706 | 24 V5OX-S | 24 V5OX-SS | 210 | 140 |



Steel, stainless steel and brass Triple-Lok® parts are delivered with NBR elastomeric seals as standard. For more details on other seal materials see page K92.

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.