
## V8OMLO 45° male stud elbow

O-Lok® ORFS tube end / Male metric thread – O-ring + retaining ring




| Tube O.D. mm | Tube O.D. in. | Thread metric T8 | Thread UN/UNF-2A T | B1 mm | D mm | D2 mm | JJ* mm | P mm | N mm | XX mm | Weight (steel) g/1 piece | O-Lok® Steel | PN (bar) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 6 | 1/4 | M 12×1.5 | 9/16-18 | 17 | 4.5 | 4 | 14 | 16 | 30 | 19 | 44 | **4M12V8OMLOS** | 250 |
| 10 | 3/8 | M 16×1.5 | 11/16-16 | 19 | 6.5 | 7 | 19 | 19 | 33 | 19 | 82 | **6M16V8OMLOS** | 250 |
| 12 | 1/2 | M 14×1.5 | 13/16-16 | 17 | 9.5 | 6 | 19 | 20 | 32 | 21 | 92 | **8M14V8OMLOS** | 250 |
| 12 | 1/2 | M 18×1.5 | 13/16-16 | 22 | 9.5 | 9 | 19 | 20 | 37 | 21 | 110 | **8M18V8OMLOS** | 250 |
| 14, 15, 16 | 5/8 | M 18×1.5 | 1-14 | 22 | 12.5 | 9 | 27 | 24 | 43 | 27 | 160 | **10M18V8OMLOS** | 250 |
| 14, 15, 16 | 5/8 | M 22×1.5 | 1-14 | 27 | 12.5 | 12 | 27 | 23 | 44 | 27 | 190 | **10M22V8OMLOS** | 250 |
| 18, 20 | 3/4 | M 27×2.0 | 1 3/16-12 | 32 | 15.5 | 15 | 30 | 26 | 50 | 30 | 288 | **12M27V8OMLOS** | 250 |
| 25 | 1 | M 33×2.0 | 1 7/16-12 | 38 | 20.5 | 20 | 36 | 30 | 52 | 32 | 300 | **16M33V8OMLOS** | 140 |
| 28, 30, 32 | 1 1/4 | M 42×2.0 | 1 11/16-12 | 50 | 26 | 26 | 41 | 32 | 54 | 33 | 444 | **20M42V8OMLOS** | 140 |
| 35, 38 | 1 1/2 | M 48×2.0 | 2-12 | 55 | 32 | 32 | 50 | 37 | 56 | 32 | 568 | **24M48V8OMLOS** | 140 |

Product delivered with NBR TRAP seal. Replacement of TRAP seal is with a standard NBR O-ring – see page J74–J75.

Part numbers shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10}$ = PN (MPa)

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.
*JJ may vary in stainless steel



Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark