

2244N – High pressure hose



CONSTRUCTION

Core tube : Polyamide
Pressure reinforcement : Two spiral layers, one braided layer of high tensile steel wire
Cover : Polyurethane
Standard colour : Black

TEMPERATURE RANGE

-10°C up to +70°C

Design Factor >2:1

#													
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m		
2244N-06V10W	10	-06	9.7	3/8	18.0	86	12,470	215	31,175	120	0.50		
2244N-08V10W	12	-08	12.8	1/2	22.7	88	12,760	220	31,900	150	0.80		

NOTES –

2244N – High pressure hose



CONSTRUCTION

Core tube : Polyamide
Pressure reinforcement : Two spiral layers, one braided layer of high tensile steel wire
Cover : Polyurethane
Standard colour : Black

TEMPERATURE RANGE

-40°C up to +100°C

Design Factor 4:1

#											
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m
2244N-025V00	4	-025	3.9	5/32	9.6	75.0	10,875	300	43,500	55	0.19
2244N-06V00	10	-06	9.8	3/8	18.0	53.5	7,755	215	31,175	120	0.50
2244N-08V10	12	-08	12.9	1/2	22.7	55.0	7,975	220	31,900	150	0.80

NOTES –