

B

Hoses with design factor 4:1
2388N

2388N – High pressure hose









Design Factor 4:1

CONSTRUCTION

- Core tube** : Polyamide
- Pressure reinforcement** : Two spiral layers and two open spiral layers of high tensile steel wire
- Cover** : Polyurethane
- Standard colour** : Black

TEMPERATURE RANGE


-40°C up to +100°C

| # |  | | | |  | |  | |  | |  | |  |
|-------------|---|------|-----|------|---|-----|---|-----|---|----|---|--|---|
| | DN | size | mm | inch | mm | MPa | psi | MPa | psi | mm | kg/m | | |
| 2388N-04V00 | 6 | -04 | 6.3 | 1/4 | 13.4 | 80 | 11,600 | 320 | 46,400 | 80 | 0.30 | | |

NOTES -



2388N – High pressure hose



CONSTRUCTION

Core tube : Polyamide

Pressure reinforcement : Two spiral layers and two open spiral layers of high tensile steel wire

Cover : Polyurethane

Standard colour : Blue

TEMPERATURE RANGE -10°C up to +70°C


Design Factor >2:1

| # | | | | | | | | | | | | | |
|--------------|----|------|-----|------|------|-----|--------|-----|--------|----|------|--|--|
| | DN | size | mm | inch | mm | MPa | psi | MPa | psi | mm | kg/m | | |
| 2388N-04V12W | 6 | -04 | 6.3 | 1/4 | 13.4 | 128 | 18,560 | 320 | 46,400 | 80 | 0.30 | | |

NOTES -

Hoses with design factor >2:1
2388N

2388N – High pressure hose









CONSTRUCTION

- Core tube** : Polyamide
- Pressure reinforcement** : Two spiral layers and two open spiral layers of high tensile steel wire
- Cover** : Polyurethane
- Standard colour** : Blue

TEMPERATURE RANGE -10°C up to +70°C

Design Factor >2:1

| # |  | | | |  |  | |  | |  |  |
|--------------|---|------|------|------|---|---|--------|---|--------|---|---|
| | DN | size | mm | inch | mm | MPa | psi | MPa | psi | mm | kg/m |
| 2388N-08V12W | 12 | -08 | 13.0 | 1/2 | 23.0 | 110 | 15,950 | 275 | 39,875 | 100 | 0.80 |

NOTES -