2388N – High pressure hose



CONSTRUCTION

Core tube	: Polyamide
Pressure reinforcement	: Two spiral layers and two open spiral layers of high tensile steel wire
Cover	: Polyurethane
Standard colour	: Black

TEMPERATURE RANGE -40°C up to +100°C

#											
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m
2388N-04V00	6	-04	6.3	1/4	13.4	80	11,600	320	46,400	80	0.30

NOTES –

2388N – High pressure hose



CONSTRUCTION

Core tube	: Polyamide
Pressure reinforcement	: Two spiral layers and two open spiral layers of high tensile steel wire
Cover	: Polyurethane
Standard colour	: Blue


TEMPERATURE RANGE -10°C up to +70°C

#	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m
2388N-04V12W	6	-04	6.3	1/4	13.4	128	18,560	320	46,400	80	0.30

NOTES –

Hoses with design factor >2:1
2388N

2388N – High pressure hose



CONSTRUCTION

Core tube	: Polyamide
Pressure reinforcement	: Two spiral layers and two open spiral layers of high tensile steel wire
Cover	: Polyurethane
Standard colour	: Blue

TEMPERATURE RANGE -10°C up to +70°C

#	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m
2388N-08V12W	12	-08	13.0	1/2	23.0	110	15,950	275	39,875	100	0.80

NOTES –

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark