

Hoses with design factor >2:1
2640D / 2640N

2640D / 2640N – Ultra-high pressure hose



CONSTRUCTION Core tube : DN 4-8: Polyoxymethylene; DN 12-25: Polyamide
Pressure reinforcement : Six spiral layers of maximum tensile steel wire

Cover : Polyamide
Standard colour : Blue

TEMPERATURE RANGE -10°C up to +70°C
Version -HT: -10°C up to +100°C

Design Factor >2:1

#												
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m	
2640D-025V32	4	-025	3.9	5/32	12.0	280	40,600	700	101,500	140	0.29	
2640D-03V32	5	-03	4.8	3/16	13.0	250	36,250	625	90,625	175	0.41	
2640D-04V32	6	-04	6.4	1/4	14.6	250	36,250	625	90,625	200	0.64	
2640D-05V32	8	-05	8.0	5/16	16.9	210	30,450	525	76,125	225	0.68	
2640N-08V32	12	-08	12.8	1/2	24.5	180	26,100	450	65,250	290	1.36	
2640N-12V32	20	-12	19.6	3/4	33.0	140	20,300	350	50,750	350	2.10	
2640N-16V32	25	-16	25.0	1	40.0	120	17,400	300	43,500	400	2.90	
2640N-12V62-HT	20	-12	19.8	3/4	33.0	110	15,950	275	39,875	350	2.16	

NOTES –

