

Medium Pressure
Water cleaning

Parkrimp No-Skive Hose
463

463

No-Skive Compact

High pressure water cleaning applications



- 2 wire **No-Skive** Compact design
- For water up to +120 °C constant temperature
- Suitable with **No-Skive** 46 series fittings

Primary Applications

High pressure water cleaners

Construction

Tube: Synthetic rubber

Reinforcement: Two high-tensile steel wire braids

Cover: Synthetic rubber in black or blue colour

Temperature Rangewater max. +120 °C

Fitting Series



Hose

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
					mm	MPa	psi	MPa	psi	mm	kg
463-5	8	5/16	-5	7.9	15.0	40.0	5800	120.0	17400	75	0.31
463-5-BLU	8	5/16	-5	7.9	15.0	40.0	5800	120.0	17400	75	0.31
463-6	10	3/8	-6	9.5	17.4	40.0	5800	120.0	17400	90	0.38
463-6-BLU	10	3/8	-6	9.5	17.4	40.0	5800	120.0	17400	90	0.38
463-8	12	1/2	-8	12.7	20.6	35.0	5075	105.0	15225	110	0.48
463-8-BLU	12	1/2	-8	12.7	20.6	35.0	5075	105.0	15225	110	0.48

WKS rubber hand grip for No-Skive high pressure water cleaning hoses can be found on page Eb-16.

The combination of high temperature and high pressure could reduce the hose life.

Also available on reels under part number 463-xx-RL

Hose layline example

PARKER NO-SKIVE 463-5 WP 40,0 MPa (5800 PSI) 1" x 8 mm (5/16) max. 120°C WATER



Ca-25

Catalogue 4400/UK