# 463

## *No-Skive* Compact

High pressure water cleaning applications




- 2 wire *No-Skive* Compact design
- For water up to +120 °C constant temperature
- Suitable with *No-Skive* 46 series fittings

## Primary Applications

High pressure water cleaners

## Construction

Tube: Synthetic rubber
Reinforcement: Two high-tensile steel wire braids
Cover: Synthetic rubber in black or blue colour

## Temperature Range ..... water max. +120 °C

Fitting Series 46

| Part Number | Hose I.D. | | | | Hose O.D. | Pressure Rating: max. working pressure | | Pressure Rating: min. burst pressure | | min. bend radius | weight |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | DN | Inch | Size | mm | mm | MPa | psi | MPa | psi | mm | kg |
| 463-5 | 8 | 5/16 | -5 | 7.9 | 15.0 | 40.0 | 5800 | 120.0 | 17400 | 75 | 0.31 |
| 463-5-BLU | 8 | 5/16 | -5 | 7.9 | 15.0 | 40.0 | 5800 | 120.0 | 17400 | 75 | 0.31 |
| 463-6 | 10 | 3/8 | -6 | 9.5 | 17.4 | 40.0 | 5800 | 120.0 | 17400 | 90 | 0.38 |
| 463-6-BLU | 10 | 3/8 | -6 | 9.5 | 17.4 | 40.0 | 5800 | 120.0 | 17400 | 90 | 0.38 |
| 463-8 | 12 | 1/2 | -8 | 12.7 | 20.6 | 35.0 | 5075 | 105.0 | 15225 | 110 | 0.48 |
| 463-8-BLU | 12 | 1/2 | -8 | 12.7 | 20.6 | 35.0 | 5075 | 105.0 | 15225 | 110 | 0.48 |

WKS rubber hand grip for No-Skive high pressure water cleaning hoses can be found on page Eb-16.
The combination of high temperature and high pressure could reduce the hose life.
Also available on reels under part number 463-xx-RL

Hose layline example

PARKER NO-SKIVE 463-5 WP 40,0 MPa (5800 PSI) I ° ° 8 mm (5/16) max. 120°C WATER





Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark