

## 520N – Standard hydraulic hose

Performance exceeds SAE 100 R8 /  
ISO 3949 Type R8 / DIN EN 855 Type R8



### MAIN FEATURES

- Very small hose outer diameters
- Excellent abrasion resistance
- Small bend radii
- Low weight
- Excellent chemical resistance due to polyamide core tube

### APPLICATIONS

High pressure service for general industrial and mobile hydraulic applications as well as with gases. Usable for a wide variety of fluids due to the polyamide core tube.

Version with white cover: **saltwater-proof, additionally improved UV resistance**, and therefore perfectly suited for boats and yachts.

### CONSTRUCTION

Core tube : Polyamide  
Pressure reinforcement : One braided layer of high tensile aramide fibre

Cover : Polyurethane, pinpricked  
Colour : black

### TEMPERATURE RANGE

-40°C up to +100°C for petroleum or synthetic hydraulic fluids.

Part No. #	DN	size	mm	inch	mm	Max. working pressure MPa / psi	Min. burst pressure MPa / psi	Min. bend radius mm	Weight kg/m	Fittings
520N-3	5	-03	4.8	3/16	10.6	34.5 5,000	138.0 20,000	38	0.07	56
520N-4	6	-04	6.3	1/4	12.7	34.5 5,000	138.0 20,000	51	0.10	56
520N-5	8	-05	7.9	5/16	14.5	31.0 4,500	124.0 18,000	64	0.12	56
520N-6	10	-06	9.5	3/8	16.1	27.5 4,000	110.0 16,000	64	0.13	56
520N-8	12	-08	12.7	1/2	20.4	24.0 3,500	96.0 14,000	102	0.20	56

### NOTES

- Also available as twinline or multiline hose, see page XVI.
- Not recommended for forklift boom applications.