

High Pressure
High abrasion resistance

Parkrimp No-Skive Hose
731TC

731TC

No-Skive Multispiral

ISO 3862 Type 4SH – EN 856 Type 4SH



- **No-Skive** hose construction
- Reinforcement of four high tensile steel wires
- Highly abrasion resistant **TOUGH COVER**
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages **Ab-16** to **Ab-19**

Applicable Specifications

ISO 3862 Type 4SH – EN 856 Type 4SH

Construction

Inner Tube: Synthetic rubber
Reinforcement: Four spirals high-tensile steel wire
Cover: Highly abrasion resistance
MSHA approved synthetic rubber

Recommended Fluids

Hydraulic fluids on a mineral-oil basis, water-glycol and lubricating oils, air and water. For air and gas applications with a pressure exceeding 1.7 MPa, the cover must be pin-pricked. Consult the chemical compatibility section on pages **Ab-26** to **Ab-34** for more detailed information.

Temperature Range -40 °C up to +100 °C

Exception: Air max. +70 °C
Water max. +85 °C

Fitting Series



Part Number	Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	DN	Inch	Size	mm		max. working pressure MPa	psi	min. burst pressure MPa	psi		
731TC-12	19	3/4	-12	19,1	32,0	42,0	6000	168,0	24000	280	1,72
731TC-16	25	1	-16	25,4	39,0	38,0	5500	152,0	22000	340	2,14
731TC-20	31	1 1/4	-20	31,8	45,0	32,0	4700	130,0	18800	460	2,96
731TC-24	38	1 1/2	-24	38,1	53,0	29,0	4200	116,0	16800	560	3,20
731TC-32	51	2	-32	50,8	68,0	25,0	3600	100,0	14400	700	5,30

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker TOUGH COVER 731TC-12 WP 42.0 MPa (6000 PSI) MSHA IC 40/26 | • • 19 mm (3/4) X 4S EN856-4SH



Dab-16

Catalogue 4400/UK