837PU-*Plus*

Hybrid Push-Lok

For a variety of high demanding applications



- High level of hose flexibility
- High abrasion resistance
- High torsion resistance
- Free from wetting disturbing substances (LABS free)
- Low push-in forces

Primary Applications

All Markets: For high demand applications
For energy chain systems
Robot and Automotive market:
For hose bundle systems

Restrictions

Not permitted for use in air brake systems and high dynamic pulsation systems.
Not recommended for fuels, mineral based hydraulic and lubricating oils and water-oil-emulsion.

Construction

Tube: Synthetic rubber
Reinforcement: High-tensile fibre braid
Cover: High performance polyurethane material in different colours

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Air, dry air, water and water-glycol-emulsions.
Consult the chemical compatibility section in catalogue C4400/UK, pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

82

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
837PU-4-XXX-RL	6	1/4	-4	6.4	12.7	1.6	235	6.4	940	95	30	0.11
837PU-6-XXX-RL	10	3/8	-6	9.5	15.9	1.6	235	6.4	940	95	50	0.15
837PU-8-XXX-RL	12	1/2	-8	12.7	19.8	1.6	235	6.4	940	95	70	0.26
837PU-10-XXX-RL	16	5/8	-10	15.9	23.0	1.6	235	6.4	940	51	90	0.27
837PU-12-XXX-RL	19	3/4	-12	19.1	26.2	1.6	235	6.4	940	51	110	0.33
837PU-16-XXX-RL	25	1	-16	25.4	32.5	1.6	235	6.4	940	51	180	0.52

* The vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
Note: When ordering, please replace in the part number XXX with the relavant colour code. Example: 837PU-4-GRN-RL

Colour codes
BLK = black
BLU = blue
RED = red
GRN = green
GRA = grey

RL = only available on reels



Hose layline example

PARKER PUSH-LOK 837PU-*Plus*-8 WP 1,6 MPa (235 PSI) I ° ° 12,5 mm (1/2)

Tel: +45 63 12 83 00 | Email: ps@hymatik.com | www.hymatik.com | Hvidkaervej 27a, DK-5250 Odense SV, Denmark