

ESH250Plus & ESH250Plus2 – Sewer cleaning hose



CONSTRUCTION

Core tube : Thermoplast
 Pressure reinforcement : High tensile synthetic fiber

Cover : Polyurethane,
 Standard colour : Green

TEMPERATURE RANGE -10°C up to +50°C

Design Factor >2:1

#											
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	
ESH250Plus-08	12	-08	12.4	1/2	21.2	25	3,625	62.5	9,060	100	0.24
ESH250Plus-12	20	-12	19.0	3/4	28.6	25	3,625	62.5	9,060	125	0.40
ESH250Plus2-16	25	-16	25.4	1	36.5	25	3,625	62.5	9,060	150	0.60
ESH250Plus2-20	32	-20	32.0	1 1/4	46.0	25	3,625	62.5	9,060	225	1.00

Ready-to-install assemblies (further lengths available upon request)

#	Length (m)								Fittings	
	Standard								BSP female swivel	BSP male
	80	100	120	160	180	200	220	240		
ESH250Plus-08	•	•	•	•	•	•	•	•	G 1/2	G 1/2
ESH250Plus-12	•	•	•	•	•	•	•	•	G 3/4	G 3/4
ESH250Plus2-16	•	•	•	•	•	•	•	•	G 1	G 1
ESH250Plus2-20	•	•	•	•	•	•	•	•	G 1 1/4	G 1 1/4

- NOTES**
- Standard available hose assemblies see table above. Ordering example: ESH250Plus-12-160
 - Crimp your own assembly: ESH250Plus(2) available as bulk hose on a drum
 - Crimp on a Parkrimp system or on a free adjustable crimper
 - To crimp ES fittings -16 and -20 use Parkrimp dies 80C-F16ES and 80C-F20ES