

High Pressure
High abrasion resistance

ParLock Hose
H31TC

H31TC

ParLock Multispiral

Exceeds ISO 3862 Type 4SP –
EN 856 Type 4SP

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages **Ab-16** to **Ab-19**

Applicable Specifications

Exceeds ISO 3862 Type 4SP – EN 856 Type 4SP

Construction

Inner Tube: Synthetic rubber
Reinforcement: Four spirals high-tensile steel wire
Cover: Highly abrasion resistance
MSHA approved synthetic rubber

Temperature Range -40 °C up to +100 °C

Exception: Air max. +70 °C
Water max. +85 °C



- Interlock technology
- Reinforcement of four high tensile steel wires
- Highly abrasion resistant **TOUGH COVER**
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Recommended Fluids

Hydraulic fluids on a mineral-oil basis, water-glycol and lubricating oils, air and water. For air and gas applications with a pressure exceeding 1.7 MPa, the cover must be pin-pricked. Consult the chemical compatibility section on pages **Ab-26** to **Ab-34** for more detailed information.

Fitting Series

External skiving (size -4 up to -8)

Internal and external skiving (size -10 up to -16)



Part Number	Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	DN	Inch	Size	mm		max. working pressure MPa	psi	min. burst pressure MPa	psi		
H31TC-4	6	1/4	-4	6,4	17,8	50,0	7250	200,0	29000	120	0,73
H31TC-6	10	3/8	-6	9,5	21,4	44,5	6450	178,0	25800	130	0,91
H31TC-8	12	1/2	-8	12,7	24,6	41,5	6000	166,0	24000	180	1,08
H31TC-10	16	5/8	-10	15,9	28,5	39,0	5650	156,0	22600	225	1,39
H31TC-12	19	3/4	-12	19,1	32,0	35,0	5000	140,0	20300	280	1,73
H31TC-16	25	1	-16	25,4	39,7	31,0	4500	124,0	18000	355	2,31

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



Dab-24

Catalogue 4400/UK