

High Pressure
High abrasion resistance

ParLock Hose
R50TC/R56TC

R50TC/R56TC

ParLock Multispiral

Exceeds ISO 3862 Type R15 –
Parker Specifications

Primary Applications

Mobile hydraulic equipment and agricultural machines
with typically large constructions.

Type Approvals

Details please find on pages **Ab-16** to **Ab-19**

Applicable Specifications

Exceeds ISO 3862 Type R15 – Parker Specifications

Construction

Inner Tube: Synthetic rubber
Reinforcement: Four or six spirals high-tensile steel wire
Cover: Highly abrasion resistance
MSHA approved synthetic rubber

Temperature Range -40 °C up to +100 °C

Exception: Air max. +70 °C
Water max. +85 °C



Recommended Fluids

Hydraulic fluids on a mineral-oil basis, water-glycol and lubricating oils, air and water. For air and gas applications with a pressure exceeding 1.7 MPa, the cover must be pin-pricked. Consult the chemical compatibility section on pages **Ab-26** to **Ab-34** for more detailed information.

Fitting Series Internal and external skiving
R56TC-6 and R56TC-8

R50TC-10 up to -16


R50TC-20



Part Number	Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	DN	Inch	Size	mm		max. working pressure MPa	psi	min. burst pressure MPa	psi		
R56TC-6	10	3/8	-6	9,5	21,8	56,0	8100	224,0	32400	130	0,95
R56TC-8	12	1/2	-8	12,7	25,5	56,0	8100	224,0	32400	180	1,25
R50TC-10	16	5/8	-10	15,9	28,50	50,0	7250	200,0	29000	225	1,48
R50TC-12	19	3/4	-12	19,1	32,00	50,0	7250	200,0	29000	270	1,85
R50TC-16	25	1	-16	25,4	38,40	50,0	7250	200,0	29000	300	2,70
R50TC-20	31	1 1/4	-20	31,8	52,60	50,0	7250	200,0	29000	450	5,00

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



Dab-31

Catalogue 4400/UK

ParLock Hose