



1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°



Part Number	Hose I.D.				Thread metric	Tube O.D. mm	A mm	B mm	E mm	W mm
	DN	Inch	Size	mm						
11C43-8-6	10	3/8	-6	9,5	M16x1,5	8	67	38	37	19
11C43-12-6	10	3/8	-6	9,5	M20x1,5	12	65	35	37	24
11C43-14-6	10	3/8	-6	9,5	M22x1,5	14	64	35	37	27
11C43-16-8	12	1/2	-8	12,7	M24x1,5	16	72	37	45	30
11C43-20-10	16	5/8	-10	15,9	M30x2	20	79	40	48	36
11C43-25-10	16	5/8	-10	15,9	M36x2	25	85	46	52	46
11C43-20-12	19	3/4	-12	19,1	M30x2	20	89	50	58	36
11C43-25-12	19	3/4	-12	19,1	M36x2	25	89	49	59	46
11C43-25-16	25	1	-16	25,4	M36x2	25	109	64	69	46
11C43-30-16	25	1	-16	25,4	M42x2	30	115	68	76	50

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version, Working temperature from -40 °C up to +105 °C. Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for hose types, depending on size: Also available in stainless steel. Details can be found in CAT 4400.1/UK

43	304	387	387ST	387TC	421WC	426	487	487ST	487TC	722	722CLF	722LT	722TC	722ST	...
	787	787TC	787ST	797	797TC	797ST	881								

