


Medium Pressure
DIN – Metric

Parkrimp No-Skive Fittings
43 Series

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS



Part Number	Hose I.D.				Thread metric	Tube O.D. mm	A mm	B mm	W mm
	DN	Inch	Size	mm					
1C943-10-6	10	3/8	-6	9,5	M18x1,5	10	50	21	22
1C943-12-6	10	3/8	-6	9,5	M20x1,5	12	52	22	24
1C943-14-6	10	3/8	-6	9,5	M22x1,5	14	50	21	27
1C943-12-8	12	1/2	-8	12,7	M20x1,5	12	60	25	24
1C943-16-8	12	1/2	-8	12,7	M24x1,5	16	59	24	30
1C943-16-10	16	5/8	-10	15,9	M24x1,5	16	66	27	30
1C943-20-10	16	5/8	-10	15,9	M30x2	20	66	27	36
1C943-20-12	19	3/4	-12	19,1	M30x2	20	66	27	36
1C943-25-12	19	3/4	-12	19,1	M36x2	25	68	28	46
1C943-25-16	25	1	-16	25,4	M36x2	25	78	33	46
1C943-30-16	25	1	-16	25,4	M42x2	30	80	33	50

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C. Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

43 Series

Approved **fitting series** for hose types, depending on size: Also available in stainless steel. Details can be found in CAT 4400.1/UK

43	304	387	387ST	387TC	421WC	426	487	487ST	487TC	722	722CLF	722LT	722TC	722ST	...
	787	787TC	787ST	797	797TC	797ST	881								



Cc-3

Catalogue 4400/UK