



Medium Pressure
DIN – Metric

Parkrimp No-Skive Fittings
43 Series

CA **Female Metric 24°
Light Series with O-Ring
Swivel – Straight**
ISO 12151-2-SWS-L – DKOL



Part Number	Hose I.D.				Thread metric	Tube O.D. mm	A mm	B mm	W mm
	DN	Inch	Size	mm					
1CA43-10-6	10	3/8	-6	9,5	M16x1,5	10	53	24	19
1CA43-12-6	10	3/8	-6	9,5	M18x1,5	12	49	19	22
1CA43-15-8	12	1/2	-8	12,7	M22x1,5	15	56	21	27
1CA43-18-10	16	5/8	-10	15,9	M26x1,5	18	61	22	32
1CA43-22-10	16	5/8	-10	15,9	M30x2	22	64	24	36
1CA43-18-12	19	3/4	-12	19,1	M26x1,5	18	65	26	32
1CA43-22-12	19	3/4	-12	19,1	M30x2	22	63	24	36
1CA43-28-16	25	1	-16	25,4	M36x2	28	78	33	41
1CA43-35-16	25	1	-16	25,4	M45x2	35	76	31	50

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version, Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request, O-ring dimensions and part-numbers see in section Eb.

43 Series

Approved **fitting series** for hose types, depending on size: Also available in stainless steel. Details can be found in CAT 4400.1/UK

43	304	387	387ST	387TC	421WC	426	487	487ST	487TC	722	722CLF	722LT	722TC	722ST	...
	787	787TC	787ST	797	797TC	797ST	881								



Cc-1

Catalogue 4400/UK