



CE Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE -L – DKOL 45°



Part Number	Hose I.D.			Thread metric	Tube O.D. mm	A mm	B mm	E mm	W mm
	Inch	Size	mm						
1CE26-10-6	5/16	-6	8,0	M16x1,5	10	66	45	17	19
1CE26-12-6	5/16	-6	8,0	M18x1,5	12	66	45	17	22
1CE26-12-8	13/32	-8	10,0	M18x1,5	12	60	39	17	22
1CE26-15-8	13/32	-8	10,0	M22x1,5	15	60	39	17	27
1CE26-18-10	1/2	-10	12,5	M26x1,5	18	68	46	20	32
1CE26-18-12	5/8	-12	16,0	M26x1,5	18	73	50	22	32
1CE26-22-12	5/8	-12	16,0	M30x2	22	77	55	26	36
1CE26-28-16	7/8	-16	22,0	M36x2	28	105	78	33	41

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for hose types:

26 201 206 213 221FR 285 293



B2b-1

Catalogue 4400/UK