



## CE Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE -L – DKOL 45°



43 Series

| Part Number | Hose I.D. |      |      |      | Thread<br>metric | Tube<br>O.D.<br>mm | A<br>mm | B<br>mm | E<br>mm | W<br>mm |
|-------------|-----------|------|------|------|------------------|--------------------|---------|---------|---------|---------|
|             | DN        | Inch | Size | mm   |                  |                    |         |         |         |         |
| 1CE43-12-6  | 10        | 3/8  | -6   | 9.5  | M18x1.5          | 12                 | 69      | 39      | 19      | 22      |
| 1CE43-15-8  | 12        | 1/2  | -8   | 12.7 | M22x1.5          | 15                 | 81      | 46      | 22      | 27      |
| 1CE43-18-10 | 16        | 5/8  | -10  | 15.9 | M26x1.5          | 18                 | 89      | 49      | 23      | 32      |
| 1CE43-22-12 | 19        | 3/4  | -12  | 19.1 | M30x2            | 22                 | 98      | 58      | 26      | 36      |
| 1CE43-28-16 | 25        | 1    | -16  | 25.4 | M36x2            | 28                 | 127     | 80      | 34      | 41      |

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.  
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for hose types, depending on size: Also available in stainless steel. Details can be found in CAT 4400.1/UK

|           |     |       |       |       |       |       |     |       |       |     |        |       |       |       |     |
|-----------|-----|-------|-------|-------|-------|-------|-----|-------|-------|-----|--------|-------|-------|-------|-----|
| <b>43</b> | 304 | 387   | 387ST | 387TC | 421WC | 426   | 487 | 487ST | 487TC | 722 | 722CLF | 722LT | 722TC | 722ST | ... |
|           | 787 | 787TC | 787ST | 797   | 797TC | 797ST | 881 |       |       |     |        |       |       |       |     |



Cc-1

Catalogue 4400/UK