



Low Pressure
DIN – Metric

Parkrimp No-Skive Fittings
26 Series

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°



Part Number	Hose I.D.			Thread metric	Tube O.D. mm	A mm	B mm	E mm	W mm
	Inch	Size	mm						
1CF26-8-4	3/16	-4	5,0	M14x1,5	8	48	28	29	17
1CF26-10-5	1/4	-5	6,3	M16x1,5	10	55	36	29	19
1CF26-10-6	5/16	-6	8,0	M16x1,5	10	55	34	31	19
1CF26-12-6	5/16	-6	8,0	M18x1,5	12	56	35	35	22
1CF26-12-8	13/32	-8	10,0	M18x1,5	12	50	30	31	22
1CF26-15-8	13/32	-8	10,0	M22x1,5	15	58	38	41	27
1CF26-18-10	1/2	-10	12,5	M26x1,5	18	57	34	38	32
1CF26-18-12	5/8	-12	16,0	M26x1,5	18	69	46	45	32
1CF26-22-12	5/8	-12	16,0	M30x2	22	78	55	47	36
1CF26-18-16	7/8	-16	22,0	M26x1,5	18	92	65	70	32
1CF26-28-16	7/8	-16	22,0	M36x2	28	96	70	71	41
1CF26-28-20	1 1/8	-20	29,0	M36x2	28	117	90	81	41
1CF26-35-20	1 1/8	-20	29,0	M45x2	35	117	90	77	50
1CF26-35-24	1 3/8	-24	35,0	M45x2	35	117	89	79	50

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for hose types:

26 201 206 213 221FR 285 293



B2b-2

Catalogue 4400/UK