

720 bar

703-Series

Max. Working Pressure Connected bar

Body Size

1/8"

bar

720

High Pressure

Parker

Parker Profile

Technical Description

Quick Coupling System with coaxial function to connect two independent lines (pressure line and return line). Available as Twin-Hose solution and Hose-in-Hose solution.

The Parker "Coaxial Hose Package" is completely assembled with a Hose-in-Hose coupling and plug, and pre-filled with hydraulic oil.

TÜV approval according to NFPA 1936:2010 and DIN EN 13204:2012.

Advantages

- With Safety locking sleeve Dry-break solution with extremely low dead space volume
- · Easy to handle no connecting against remaining pressure
- · Sealed sleeve protects against dust and dirt
- Coupling and plug assembled with dust caps (POM black) and stainless steel wire

Applications

- Hydraulic cutter and spreader Hydraulic saw
- Rerail systems
- Rescue equipment

Working Temperature


-30°C up to +100°C (NBR) depending on the medium. Special seals are available on request.

Safety Note

A reliable functioning for the hose-in-hose solution can only be guaranteed in conjunction with original Parker Coaxial-Hose.

Patent pending.							
Material Coupling	Standard						
Coupling Body	Steel zinc plated						
Back Body	High-strength Aluminium						
Sleeve	Aluminium						
Seals	NBR						
Material Plug	Standard						
Plug Body	Steel chemical-nickel plated with PTFE-coating						
Back body	High-strength Aluminium						
Seals	NBR						

Flow Capacity with Oil with Viscosity of 32cSt at 40°C as per ISO 7241/2-2000




Working Pressure

Pressure Line Return Line

720 bar

35 bar



Coupling								703-Series
	Connection A	L mm	L1 mm	D mm	D1 mm	B mm	Weight gr.	Part Number
	M 12 x 1,5	102	13	48	50	41	475	703KBIM12SPZR
Twin-Hose								
	M 27 x 1,5	95	10,5	48		37	425	703KBIM27SPZR
Hose-in-Hose								

Plug

Connection L L1 D D1 в Weight Part Number А mm mm mm mm mm gr. M 12 x 1,5 92 13 30 50 41 308 703SBIM12SPZR 6. 0 Twin-Hose M 27 x 1,5 10,5 30 35 245 703SBIM27SPZR 85 40 Hose-in-Hose

Hose Package - Completely assembled

	Inside Hose (Pressure Line) Inside x Outside ø mm	Outside Hose (Return Line) Inside x Outside ø mm	Working Length m	Part Number
	4,8 x 10,7	16,8 x 23,2	5	703SET5R
	4,8 x 10,7	16,8 x 23,2	10	703SET10R
	4,8 x 10,7	16,8 x 23,2	15	703SET15R
with 703KBIM27SPZR and 703SBIM27SPZR				

 Λ Please consider our security advices on the pages 12/13 Λ

131

hymatik

720 bar

High Pressure

Ь

703-Series

703-Series