


Other designs in series 27

The following other designs can be found from page:

- Stainless Steel P. 156
- Safety Self-Venting P. 232

Interchangeability (KA only)

- Rectus 41
- Rectus 1700
- Rectus 1727
- Cejn 410

1/2" universal industrial coupling with standard European profile for use with large pneumatic consumers. Coupling system with single-hand operation. High Flow valve for optimum flow and low pressure drop. The series stands out for its robust design (steel sleeve), extremely high flow and long service life even with the harshest use. The collar design minimises damage to the valve body.

Series 27 in brass material with nickel plating and with additional end connections available on request.

Dust Protections (P. 250)
for Coupling Part.-No. SK27S

Working Temperature*
-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.


Working Pressure**

35 bar
** maximum static working pressure with design factor 4 to 1.

35 bar

Material

Coupling: Brass / Steel nickel plated
Plug: Steel nickel plated
Seals: NBR

Coupling: Brass
Plug: Brass nickel plated
Seals: NBR

Technical Description





Connecting Force 0 bar: 60 N
Connecting Force 6 bar: 180 N

Vacuum Coupling: 87%
Available on request with O-ring seal for vacuum when coupled.

Dead space volume: 2,2 ml

Connecting Force 0 bar: 60 N
Connecting Force 6 bar: 180 N




Vacuum Coupling: 96%
Vacuum Plug: 96%
Available on request with O-ring seal for vacuum when coupled.

Flow diagrams




Couplings – with valve




Series 27KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	R 1/4	24	63	12	27	27KAAK13MPN
	R 3/8	24	63	12	27	27KAAK17MPN
	R 1/2	24	65	17	27	27KAAK21MPN
	R 3/4	27	65	17	27	27KAAK26MPN
 Female Thread	G 1/4	24	56	10	27	27KAIW13MPN
	G 3/8	24	56	11	27	27KAIW17MPN
	G 1/2	24	56	12	27	27KAIW21MPN
	G 3/4	27	60	16	27	27KAIW26MPN
 Hose Barb	6 mm	24	76	25	27	27KATF06MPN
	8 mm	24	76	25	27	27KATF08MPN
	9 mm	24	76	25	27	27KATF09MPN
	10 mm	24	76	25	27	27KATF10MPN
	13 mm	24	76	25	27	27KATF13MPN
	16 mm	24	76	20	27	27KATF16MPN
	19 mm	24	76	25	27	27KATF19MPN



Plugs – without valve

Series 27KA




	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	R 1/4	17	40	12		27SFAK13SXX
	R 3/8	17	40	12		27SFAK17SXX
	R 1/2	22	45	17		27SFAK21SXX
	R 3/4	27	48	19		27SFAK26SXX
 Female Thread	G 1/4	17	33	9		27SFIW13SXX
	G 3/8	19	33	12		27SFIW17SXX
	G 1/2	24	37	12		27SFIW21SXX
	G 3/4	32	42	16		27SFIW26SXX
 Hose Barb	6 mm		48	25	15	27SFTF06SXX
	8 mm		48	25	15	27SFTF08SXX
	9 mm		48	25	15	27SFTF09SXX
	10 mm		48	25	15	27SFTF10SXX
	13 mm		48	25	15	27SFTF13SXX
	16 mm		49	25	18	27SFTF16SXX
	19 mm		49	25	21	27SFTF19SXX

⚠ Please consider our security advices on the pages 12/13 ⚠




Brass/Steel

Low Pressure


Couplings – with valve
Series 27KB

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	R 1/4	24	63	12	27	27KBAK13BPN
	R 3/8	24	63	12	27	27KBAK17BPN
	R 1/2	24	65	17	27	27KBAK21BPN
	R 3/4	27	65	17	27	27KBAK26BPN
 Female Thread	G 1/4	24	56	10	27	27KBIW13BPN
	G 3/8	24	56	11	27	27KBIW17BPN
	G 1/2	24	56	12	27	27KBIW21BPN
	G 3/4	32	60	16	27	27KBIW26BPN
 Hose Barb	8 mm	24	76	25	27	27KBTF08BPN
	9 mm	24	76	25	27	27KBTF09BPN
	10 mm	24	76	25	27	27KBTF10BPN
	13 mm	24	76	25	27	27KBTF13BPN
	16 mm	24	76	25	27	27KBTF16BPN
	19 mm	24	76	25	27	27KBTF19BPN


Plugs – with valve
Series 27KB

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	R 1/4	24	60,5	12		27SBAK13MPN
	R 3/8	24	60,5	12		27SBAK17MPN
	R 1/2	24	62,5	17		27SBAK21MPN
	R 3/4	27	62,5	17		27SBAK26MPN
 Female Thread	G 3/8	24	54,5	9		27SBIW17MPN
	G 1/2	24	54,5	12		27SBIW21MPN
	G 3/4	32	58,5	16		27SBIW26MPN
 Hose Barb	9 mm	24	74	25		27SBTF09MPN
	10 mm	24	74	25		27SBTF10MPN
	13 mm	24	74	25		27SBTF13MPN
	16 mm	24	74	25		27SBTF16MPN
	19 mm	24	74	25		27SBTF19MPN