

Brass/Steel

Nominal Diameter

10 = 80 mm²



Rectus Series

41

Low Pressure



Brass coupling with no valve for applications with liquids in the pressure range up to 35 bar. The couplings are corrosion resistant. The system stands out for a high flow with minimal pressure drop.

Series 41 with additional end connections available on request.

Working Temperature*
-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.



Working Pressure**

35 bar

** maximum static working pressure with design factor 4 to 1.

Material

Coupling: Brass nickel plated

Plug: Brass nickel plated

Seals: NBR

Technical Description

Connecting Force 0 bar: 10 N


Connecting Force 6 bar: 10 N

Interchangeability (KA only)

- Rectus 27
- Cejn 417

Flow diagrams




Water





Couplings – without valve




Series 41KF

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	G 1/2		31	8	25	41KFAW21MPN
 Female Thread	G 1/2	24	32,5	10	25	41KFIW21MPN
 Hose Barb	13 mm		48,5	25	25	41KFTF13MPN



Plugs – without valve

Series 41KF

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	G 1/2	24	40	12		41SFAW21MXN
 Female Thread	G 1/2	24	37	12		41SFIW21MXN
 Hose Barb	13 mm		48	25	15	41SFTF13MXN
	16 mm		49	25	18	41SFTF16MXN
	19 mm		49	25	21	41SFTF19MXN

⚠ Please consider our security advices on the pages 12/13 ⚠