

Nominal Diameter

4,3 - 30


Rectus Series

70


Coupling range in sizes from 1/8" to 1 1/2" with plug profile in accordance with ISO 7241-1 series B. Particularly suitable for use with liquid media. Coupling system with two-hand operation, i.e. the locking sleeve must be pushed back manually when coupling. The coupling range stands out for its high flow rates against a low pressure drop. 1 1/2" design (series 77) with locking pin and EPDM seal.

Working Temperature*
 -20°C up to +90°C (NBR)
 -40°C up to +90°C (EPDM)
 depending on the medium.

* For temperatures below -20°C and over +90°C and depending on the medium, other seal variants (FKM, FFKM) are available.

Other designs in series 70

The following other designs can be found from page:

- Brass / Steel P. 126
- Stainless Steel P. 164


Working Pressure**

see chart

** maximum static working pressure with design factor 4 to 1.

Material








Coupling: POM white
Plug: POM white
Seals: NBR

Interchangeability

• ISO 7241-1 Series B

Technical Description

See Rectus series 70 - brass/steel from page 126


Flow diagrams Water
71KB - 1/8"

72KB - 1/4"

73KB - 3/8"

74KB - 1/2"

75KB - 3/4"

76KB - 1"

77KB - 1 1/2"




Couplings – with valve

Series 70KB

Size	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	Working Pressure max. / bar	Part Number
1/4"	G 1/4	19		57,5	10		28,5		15	72KBIW13DPX
3/8"	G 3/8	22		64	11,5		35		15	73KBIW17DPX
1/2"	G 1/2	27		76	16		44,5		10	74KBIW21DPX
3/4"	G 3/4	34		96	24		55		10	75KBIW26DPX
1"	G 1	41		105,5	24		62		10	76KBIW33DPX
1 1/2"	G 1 1/2	60		133	23		76		10	77KBIW48DEXS




Female Thread



Plugs – with valve

Series 70KB

Size	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	Working Pressure max. / bar	Part Number
1/4"	G 1/4	19		35	10				15	72SBIW13DPX
3/8"	G 3/8	22		39	11,5				15	73SBIW17DPX
1/2"	G 1/2	27		48	16				10	74SBIW21DPX
3/4"	G 3/4	36		60	24				10	75SBIW26DPX
1"	G 1	41		56	24				10	76SBIW33DPX
1 1/2"	G 1 1/2	60		132	23				10	77SBIW48DEX



Female Thread

⚠ Please consider our security advices on the pages 12/13 ⚠

Thermoplastic

Low Pressure